



## Elbow 45° PVC-U metric

| d<br>(mm) | d<br>(inch) | PN<br>(bar) | Code               | SP | Weight<br>(kg) | z<br>(mm) | D<br>(mm) | L<br>(mm) |
|-----------|-------------|-------------|--------------------|----|----------------|-----------|-----------|-----------|
| 16        |             | 16          | <b>721 150 105</b> | 10 | 0.008          | 5         | 21        | 19        |
| 20        |             | 16          | <b>721 150 106</b> | 10 | 0.011          | 5         | 25        | 21        |
| 25        |             | 16          | <b>721 150 107</b> | 10 | 0.017          | 6         | 31        | 25        |
| 32        |             | 16          | <b>721 150 108</b> | 10 | 0.021          | 8         | 38        | 30        |
| 40        |             | 16          | <b>721 150 109</b> | 10 | 0.048          | 10        | 47        | 36        |
| 50        |             | 16          | <b>721 150 110</b> | 5  | 0.086          | 12        | 59        | 43        |
| 63        |             | 16          | <b>721 150 111</b> | 5  | 0.160          | 14        | 73        | 52        |
| 75        | 2 ½         | 16          | <b>721 150 112</b> | 5  | 0.253          | 17        | 87        | 61        |
| 90        |             | 16          | <b>721 150 113</b> | 4  | 0.430          | 20        | 105       | 71        |
| 110       |             | 16          | <b>721 150 114</b> | 4  | 0.750          | 25        | 127       | 86        |
| 125       |             | 16          | <b>721 150 115</b> | 1  | 1.193          | 28        | 146       | 97        |
| 140       | 5           | 16          | <b>721 150 116</b> | 1  | 1.570          | 32        | 162       | 108       |
| 160       |             | 16          | <b>721 150 117</b> | 4  | 2.280          | 36        | 185       | 122       |
| 200       |             | 10          | <b>721 150 119</b> | 2  | 3.288          | 43        | 225       | 149       |
| 225       |             | 10          | <b>721 150 120</b> | 1  | 4.191          | 49        | 250       | 168       |
| 250       |             | 10          | <b>721 150 121</b> | 1  | 7.115          | 60        | 282       | 192       |
| 280       |             | 10          | <b>721 150 122</b> | 1  | 10.340         | 66        | 318       | 213       |
| 315       |             | 6           | <b>721 150 123</b> | 1  | 14.292         | 74        | 356       | 239       |
| 400       |             | 6           | <b>721 150 125</b> | 1  | 25.268         | 94        | 442       | 302       |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>